

XNC-40s series



3GPP/ISMA support

Dual video streaming with separate frame rate/resolution/bandwidth settings for PC and mobile

Adjustable numbers of IR led control – support automatic, manual and scheduled modes.

Supports enhanced MPEG-4 compression

Supports resolution of up to 640x480 pixels at 30 fps

Free video management software CamView accompanied for easy access and multi-camera management

View the video anywhere in the Internet

Connect up to 20 users simultaneously

Motion Detection and E-mail/FTP notification

Built-in Web server for managing via standard web browser

Video recording upon event scheduling

Technical Specifications

Model	XNC-40s
Major function	outdoor IP camera
Wireless models	N/A
Dimension	130x77x78mm
Weight	498g
Micro-SD card slot	No
Image sensor	1/4" CMOS AEC, AWB, AGC
Lens Type	4.5mm, F1.9
Max Video Resolution	640x480
Frames Per Second	30
Networking	10/100 Base TX Ethernet Auto-MDIX/ RJ45
Relay input/output	1/0
Audio capability	yes
Video compression	MPEG-4 PART2 Dual stream
Light sensitivity	0.2 Lux (IR led off) 0 Lux (IR led on)
Night mode	30m IR LED ICR
Pan/Tilt	No
RS485	No
Water proof	IP66

© Xenyum security products | Data subject to change without notice

